Model	ZT30J		
	Metric	Imperial	
Size			
Work Height	32.48m	106ft 7in	
Platform Height	30.48m	100ft	
Horizontal Outreach	19.78m	64ft 11in	
A - Stowed Length	12.43m	40ft 9in	
B - Stowed Width	2.49m	8ft 2in	
C - Stowed Height	2.80m	9ft 2in	
D - Platform Length	2.44m	8ft	
E - Platform Width	0.91m	3ft	
F - Wheelbase	3.05m	10ft	
Wheelbase	2.11m	6ft 11in	
G - Ground Clearance	0.40m	1ft 4in	
Performance			

Platform Capacity (Unrestricted/R estricted)	230/340kg	507/750lb	
Drive Speed (Stowed)	5.5km/h	3.42mph	
Gradeability	45%(24°)		
Turning Radius (Inside)	3.66m	12ft	
Turning Radius (Outside)	6.86m	22ft 6in	
Turntable Swing	360°continuous		
Platform Rotation	±90°		
Tail Swing	1.47m	4ft 10in	
Jib (Range of Articulation)	130° (- 55°~75°)		
Max. Working Slope	3°		
Max. Wind Speed	12.5m/s	28mph	
Power			
Engine	Cummins QSF2.8		
Fuel Tank Capacity	200L	52.8 (us gal)	
Control Voltage	12V DC		

	T			
Hydraulic Tank Capacity	150L	39.6gal		
Drive Mode	4	4WD		
Steering Mode	Fror	Front-wheel		
Tire				
Туре				
Weig	jht			
Gross	19400kg	42731lb		
ZT30J Highlights				
Rough terrain chassis features swing axle function, easy to achieve 4 5% gradeability				
Industry's first 30-meter product without bridge extending				
Smooth & stable boom extension, the telescopic efficiency of the boom is increased by 30% compared with that of the double-cylinder telescopic boom				
Smooth & stable boom extension technique controls the minimum st able extending speed at 0.015m/s (0.034mph)				
Zoomlion AWM Romote Monitoring and Rental Managament System				
Affordable and maneuverable				
Accessories & Options				
Platform work lights				
Anti-collision device				
AC power to platform				

Features				
Standard deatures				
Horn	Platform work light			
Proportional control	Anti-collision device			
All motion alarm	AC power to platform			
Flashing amber beacon	Outrigger in- situ telescopic function (ZT34J /ZT38J/ZT42J)			
Self-closing entry gate				
Emergency descent system				
Emergency stop button				
Auto-leveling system				
On-board diagnostic system				
Tilt protection system				
Oscillating axle				
Load sensing system				
4.3' Led display				
Swing-out engine tray				